

Customer Information Sheet

DRAWING No.: SOX-46

SHEET 2 OF 2


IF IN DOUBT - ASK

(C)

NOT TO SCALE

THIRD ANGLE PROJECTION

ALL DIMENSIONS IN mm

**NOTES:**

1. THIS PRODUCT IS RECOMMENDED FOR USE WITH S8071-46R AND S8081-46R SMT CLIPS.
3. MAXIMUM BURR ON CUTTING AREA = 0.05mm.
4. ALL PRODUCT IS RoHS AND REACH COMPLIANT.
5. PACKAGING = 100 COMPONENTS PER BAG.

SPECIFICATIONS:

MATERIAL = PHOSPHOR BRONZE
FINISH = 2-4 μ TIN OVER 1-2 μ NICKEL
ELECTRICAL:
CURRENT RATING = 1.5A
VOLTAGE RATING = 250V AC/DC
CONTACT RESISTANCE = 20m Ω MAX

ORDER CODE:**SOX-46****PIN LENGTH:**

7 = 23.00
8 = 15.00

FINISH:

46 = 2-4 μ TIN OVER
1-2 μ NICKEL

PART No.	DIM 'A'
S07-46	23.00
S08-46	15.00

SB	I	17.06.15	-----
NAME	ISS.	DATE	C/NOTE
APPROVED:		S.BENNETT	
CHECKED:		M.PLESTED	
DRAWN:		S.BENNETT	
CUSTOMER REF.:			
ASSEMBLY DRG:			

HARWIN

www.harwin.com
technical@harwin.com

THIS DRAWING AND ANY
INFORMATION OR DESCRIPTIVE
MATTER SET OUT HEREON ARE
CONFIDENTIAL AND COPYRIGHT
PROPERTY OF THE HARWIN
GROUP AND MUST NOT BE
DISCLOSED, LOANED, COPIED
OR USED FOR MANUFACTURING,
TENDERING OR FOR ANY
OTHER PURPOSE WITHOUT
THEIR WRITTEN PERMISSION.

TOLERANCES

X. = ± 1 mm
X.X = ± 0.50 mm
X.XX = ± 0.10 mm
X.XXX = ± 0.01 mm

ANGLES = $\pm 5^\circ$
UNLESS STATED

MATERIAL:

SEE ABOVE

FINISH: SEE ABOVE**S/AREA:**mm²**TITLE:**

BRIDGE PIN

DRAWING NUMBER:**SOX-46**

SHT
2 OF
2

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Harwin:

[S07-46](#) [S08-46](#)