



UNO POWER power supplies
Basic functionality
compact

UNO POWER

Compact and highly efficient

Wide range of products

- for all common voltage levels

Save energy

- thanks to high efficiency of up to 94 % and low power dissipation (no-load) of less than 0.3 W

Save space

- Power density up to 325 W/dm³

High reliability

- Wide temperature range from -25 to +70 °C

UNO POWER 1~



24 DC / 150 W

UNO-PS/1AC/24DC/150W
2904376



24 DC / 240 W

UNO-PS/1AC/24DC/240W
2904372

UNO POWER 1~



24 DC / 30 W

UNO-PS/1AC/24DC/30W
2902991



24 DC / 60 W

UNO-PS/1AC/24DC/60W
2902992



24 DC / 100 W

UNO-PS/1AC/24DC/100W
2902993



24 DC / 90 W

UNO-PS/1AC/24DC/90W/C2LPS
2902994



24 DC / 90 W

UNO-PS/2AC/24DC/90W/C2LPS
2904371

48 DC / 60 W

UNO-PS/1AC/48DC/60W
2902995

48 DC / 100 W

UNO-PS/1AC/48DC/100W
2902996

15 DC / 30 W

UNO-PS/1AC/15DC/30W
2903000

15 DC / 55 W

UNO-PS/1AC/15DC/55W
2903001

15 DC / 100 W

UNO-PS/1AC/15DC/100W
2903002

12 DC / 30 W

UNO-PS/1AC/12DC/30W
2902998

12 DC / 55 W

UNO-PS/1AC/12DC/55W
2902999

12 DC / 100 W

UNO-PS/1AC/12DC/100W
2902997

5 DC / 25 W

UNO-PS/1AC/5DC/25W
2904374

5 DC / 40 W

UNO-PS/1AC/5DC/40W
2904375

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstraße 8
32825 Blomberg, Germany
Phone: +49 (0) 52 35 3-00
Fax: +49 (0) 52 35 3-4 12 00
E-mail: info@phoenixcontact.com
phoenixcontact.com